

200 SERIES WEIGHT INDICATORS

200 SERIES WEIGHT INDICATORS



MODEL NUMBER	200	204	205	210	215	220
ENCLOSURE	Aluminum	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
MOUNTING	Panel	Bracket	Bracket	Bracket	Bracket	Bracket
RATING	NEMA 12 / IP55	NEMA 12 / IP55	NEMA 4X / IP66	NEMA 4X / IP66	NEMA 4X / IP66	NEMA 4X / IP66
NUMBER OF LOAD CELLS	8 x 350 ohm	4 x 350 ohm	8 x 350 ohm	8 x 350 ohm	8 x 350 ohm	14 x 350 ohm
DISPLAY	0.6"/14 mm High 6-Digit LED	1"/25 mm High 6-Digit LCD	0.6"/14 mm High 6-Digit LED	0.6"/14 mm High 6-Digit LED	1"/25 mm High 6-Digit LCD	0.8"/20 mm High 12-Digit Backlit LCD
NUMERIC KEYPAD				✓	✓	✓ and Alpha
PUSH BUTTON TARE	✓	✓	✓	✓	✓	✓
KEYBOARD TARE				✓	✓	✓
PRESET TARES						✓ 200
DIMENSIONS	5.67" W x 9.13" D x 2.81" H / 14 cm W x 23 cm D x 71 cm H	8" W x 2.125" D x 6.625" H / 20 cm W x 5 cm D x 17 cm H	9.2" W x 2.75" D x 7.5" H / 23 cm W x 7 cm D x 19 cm H	9.2" W x 2.75" D x 7.5" H / 23 cm W x 7 cm D x 19 cm H	9.2" W x 3.125" D x 7.5" H / 23 cm W x 8 cm D x 19 cm H	10" W x 4" D x 8" H / 25 cm W x 10 cm D x 20 cm H
RS232 & 20mA CURRENT LOOP	✓ (Option)	✓	✓	✓	✓	✓
ANALOG OUTPUT (0 TO 10V OR 4 TO 20mA)	✓ (Option)		✓ (Option)	✓ (Option)	✓ (Option)	✓ (Option)
PRESET WEIGHT COMPARATOR				✓ 3	✓ 3	✓ 8
POWER	90 to 260 VAC, 50 or 60 Hz	115 VAC 60 Hz adapter or, 230 VAC 50/60 Hz, or 6 "C" Alkaline or rechargeable NiCad batteries	90 to 260 VAC, 50 or 60 Hz	90 to 260 VAC, 50 or 60 Hz	90 to 264 VAC, 50 or 60 Hz, or 10 "AA" rechargeable NiMH batteries	90 to 260 VAC, 50 or 60 Hz
PARTS COUNTING				✓	✓	✓
DISPLAYED INCREMENTS	Up to 10,000 Trade	Up to 5,000 Trade	Up to 10,000 Trade	Up to 10,000 Trade	Up to 10,000 Trade	Up to 10,000 Trade
TIME & DATE				✓	✓	✓
PRINTER OUTPUT	✓	✓	✓	✓	✓	✓
CHECKWEIGHING				✓	✓	✓
DIGITAL FILL CONTROL						✓
BATCHING						✓
NTEP CERTIFIED	01-011A2	02-16A1	01-011A2	01-011A2	01-011A2	01-011A2
OIML CERTIFIED	R76/1992-DK1-01.02	R76/1992-DK1-02.03	R76/1992-DK1-01.02	R76/1992-DK1-01.02	PENDING	R76/1992-DK1-01.02